

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc

SECTION 1 - COMPANY AND PRODUCT IDENTIFICATION

PRODUCT

Product Name: BUTYL ACETATE

Control Number: 00073

Product Description: Solvent

COMPANY IDENTIFICATION

Supplier: COLONIAL CHEMICAL SOLUTIONS, INC.

916 West Lathrop Avenue

Savannah, Georgia 31415

24 Hour Emergency Telephone: (800)-424-9300 CHEMTREC

General Information: (912) 236-1331

SECTION 2- HAZARDS IDENTIFICATION

GHS Classification:

[Health]

Specific target organ toxicity Category 3

[Environmental]

Acute aquatic toxicity Category 3

[Physical]

Flammable Liquid Category 3

GHS Label elements, including precautionary statements

Pictograms



Signal Word: Warning

Hazard statement(s)

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTSCHEMICAL

CHEMICAL NAME

CAS Number

%WT

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc

Butyl Acetate

123-86-4

90-100

SECTION 4 - FIRST AID MEASURES

Eyes: Flush with running water for several minutes. Seek medical attention if irritation persists.

Skin: Wash exposed skin with soap and water. Seek medical attention if irritation persists.

Inhalation: For excessive inhalation remove to fresh air. If breathing is difficult seek medical attention.

Ingestion: DO NOT induce vomiting. Rinse mouth with water. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Extinguishing Media: To extinguish flames use water spray, dry chemical, carbon dioxide or fire fighting foam. .

Fire Fighting Procedures: Cool exposed containers with water spray. Wear self-contained breathing apparatus (SCBA) operated in pressure demand mode and full bunker firefighter's protective clothing.

Fire and Explosion Hazards: Containers can rupture and explode under fire conditions due to pressure and vapor buildup. Heated vapors may form explosive mixture with air. Vapors may travel across the ground and reach an ignition source.

SECTION 6 - ACCIDENTAL RELEASE and DISPOSAL MEASURES

Ventilate the area and stop source of spill. Salvage and recycle as much material as possible. Eliminate sources of ignition. For small spills, use absorbent material such as towels or absorbent powders. Put all material into proper waste disposal container with lid tightly covered.

For larger spills, dike spill, recover free liquid, collect with an electrically protected vacuum cleaner or by wet-brushing, and use absorbent material to dry area and then rinse area with water. Put all material into appropriate waste containers. Avoid contaminating ground and surface water.

SECTION 7 - STORAGE AND HANDLING

Precautions To Be Taken In Handling and Storage: Avoid contact with product. Do not breath vapors.

Always store in tightly sealed, and properly labeled original container. Store in a cool, dry well ventilated area, away from acute fire hazards. Use non-sparking tools. Bond and ground all equipment to prevent static discharge during transfer.

Other Precautions: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. The level of protection and types of controls will vary depending upon potential exposure conditions.

Exposure Limits: Butyl Acetate 150 ppm ACGIH; 200 ppm OSHA

Personal Protective Equipment (PPE):

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133.

Skin: If prolonged or repeated skin contact is likely, wear appropriate protective gloves.

Clothing: Selection of protective clothing depends on work conditions.

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

Other Equipment: Adequate explosion proof ventilation to control airborne concentrations below the exposure limits. Eye wash station and drenching shower in close proximity to use are advised.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: 73 °F	Flammability Limits: Lower 2 Upper 8
Autoignition Temperature: No available data	Specific Gravity: 0.87 - 0.89
Boiling Point: 255 °F	Volatile %: No available data
Melting Point: -108 °F	Evaporation Rate (BuAc=1): No available data
Vapor Pressure: 15 mmHg	pH: 6.2
Vapor Density (Air-1): 4	Solubility in Water: 5 g/l
Odor/Appearance: Colorless liquid with fruit-like odor.	

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use and temperature conditions.

Conditions to Avoid: Keep away from heat, flame and other potential ignition sources.

Materials to Avoid: Strong acids, and oxidizers.

Decomposition Products: When combusted, oxides of carbon and various hydrocarbons.

SECTION 11 - TOXICOLOGICAL INFORMATION

Signs and Symptoms of Overexposure:

Skin: Contact can cause redness, irritation and drying. Severity depends on the amount and duration of exposure.

Eyes: Vapors may be irritating to the eyes. Liquid contact will cause stinging and tearing.

Inhalation: Excessive inhalation of high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause central nervous system depression.

Ingestion: If swallowed this material may irritate the mucous membranes of the mouth throat and esophagus. Aspiration of this material into the lungs may result in damage or death.

Acute oral toxicity:

LD50 rat: 10,700 - 14,130 mg/kg

Acute inhalation toxicity:

LC50 rat: > 21.0 mg/l 4h

Acute dermal toxicity:

LD50 rabbit: 17,600 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY: Toxicity to fish LC50 - Lepomis macrochirus (Bluegill) - 100 mg/l - 96 h

Bio-accumulative potential: Bioaccumulation of this product is unlikely. This product is readily biodegradable.

Mobility: This product is not mobile in soil and likely to volatilize from soil surface.

SECTION 13 - DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

SECTION 14 · TRANSPORTATION

U.S. DEPARTMENT OF TRANSPORTATION (Road or Rail):

Proper Shipping Name: Butyl Acetates
Hazard Class: 3
UN Number: 1123
Packaging Group: 3

SECTION 15 · REGULATORY INFORMATION

US FEDERAL REGULATIONS

Comprehensive Environmental Response and Liability Act (CERCLA)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. The reportable quantity (RQ) for this material is 5000 pounds. If appropriate, immediately report to the National Response Center (800/424-8802) as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies.

Toxic Substance Control Act (TSCA): All components of this product are listed on the TSCA inventory list.

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Chronic Health Hazard, Fire Hazard.

SARA Section 313 (40 CFR 372) Hazard Categories: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act: This product contains no chemicals that are listed under the CWA.

Clean Air Act: This product contains no chemicals that are listed under the CAA.

California Prop 65: This product contains no chemicals known by the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16 · OTHER INFORMATION

MSDS Revision Date: September 2014

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

Health: 1
Flammability: 3
Reactivity: 0

The information above is believed to be accurate and represents the best information currently available to us. However, Colonial Chemical Solutions makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Colonial be liable for any claims, losses, or damages of any third party or for

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc

lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Colonial has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this MSDS and its contents from that originally submitted by Colonial.