

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 1 - COMPANY AND PRODUCT IDENTIFICATION

PRODUCT

Product Name: DIBUTYL PHTHALATE
Control Number: 00162
Product Description: Phthalic dibutyl ester

COMPANY IDENTIFICATION

Supplier: COLONIAL CHEMICAL SOLUTIONS, INC.
916 West Lathrop Avenue
Savannah, Georgia 31415

24 Hour Emergency Telephone: (800)-424-9300 CHEMTREC
General Information: (912) 236-1331

SECTION 2- HAZARDS IDENTIFICATION

GHS Classification:

[Health]

Reproductive toxicity Category 1B

[Environmental]

Acute aquatic toxicity Category 1

[Physical]

None

GHS Label elements, including precautionary statements

Pictograms



Signal word Danger

Hazard statement(s)

H360 May damage fertility or the unborn child.
H400 Very toxic to aquatic life.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P281 Use personal protective equipment as required.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P391 Collect spillage.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS Number	%WT
Dibutyl phthalate	84-74-2	100

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 4 - FIRST AID MEASURES

FIRST AID PROCEDURES:

Eye Contact: Flush eyes with plenty of water for at least 15 minutes. Seek medical attention.

Skin Contact: Wash with soap and water. Seek medical attention if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. Seek medical attention.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.

SECTION 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous combustion products: Oxides of carbon and various hydrocarbons

Fire Fighting Procedures: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Unusual Fire and Explosion Hazards: Slightly flammable to flammable in presence of open flames and sparks, or heat.

SECTION 6 - ACCIDENTAL RELEASE and DISPOSAL MEASURES

Spills: Provide adequate ventilation. Shut off or plug source of spill.

Small spills: absorb on inert media and collect into suitable container.

Large Spills: Dike spill area to contain liquid. Salvage as much re-useable liquid as possible into a suitable container.

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for Disposal.

SECTION 7 - STORAGE AND HANDLING

Handling: Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Avoid contact with eyes. Wear suitable protective clothing. Keep away from incompatibles such as oxidizing agents, acids, alkalis.

Storage: Store in a cool, dry, ventilated area, away from incompatible substances. Store only in approved properly labeled containers. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Provide adequate mechanical ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. The level of protection and types of controls will vary depending upon potential exposure conditions.

Exposure Limits: Dibutyl phthalate

5 mg/kg ACGIH 5 mg/kg OSHA

Personal Protective Equipment (PPE):

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133.

Skin: If prolonged or repeated skin contact is likely, wear appropriate protective gloves.

Clothing: Selection of protective clothing depends on work conditions, potential exposure conditions and may include gloves, boots, suits and other protective items.

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: 340 °F
Autoignition Temperature: 932 °F
Boiling Point: 644 °F
Melting Point/Freezing Point: -31 °F
Vapor Pressure: Nil
Vapor Density (Air-1): 9.6
Odor/Appearance: Colorless to light yellow liquid with ester odor.

Flammability Limits: Not applicable
Specific Gravity: 1.046
Volatile %: Nil
Evaporation Rate (Water=1): No available data
pH: No available data
Solubility in Water: slightly, 13 mg/l

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use and temperature conditions.
Conditions to Avoid: Keep away from heat, flame and other potential ignition sources.
Incompatible Materials: Strong oxidizing agents, Nitrates, Bases, Acids, Chlorine.
Hazardous Polymerization: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Signs and Symptoms of Overexposure:

Skin: May cause skin irritation, stinging and burning sensation. It can cause dermatitis.
Eyes: Splash contact can cause immediate, severe stinging pain, and profuse tearing.
Inhalation: It can irritate the nose and throat. It may affect behavior/central nervous system
Ingestion: If swallowed this material may irritate the mucous membranes of the mouth throat and esophagus. May cause nausea, vomiting. It may affect behavior/central nervous system.

Acute oral toxicity:

LD50 rat: 8,000 mg/kg

Acute inhalation toxicity:

LD50 rat: 4,250 mg/m³

Acute dermal toxicity:

LD50 rabbit: > 20,860 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

Aquatic Toxicity: Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 0.85 mg/l - 96.0 h
Bio-accumulative potential: This product is readily biodegradable.
Mobility: Accidental spillage may lead to penetration in the soil.

SECTION 13 - DISPOSAL CONSIDERATIONS

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

SECTION 14 - TRANSPORTATION

U.S. DEPARTMENT OF TRANSPORTATION (Road or Rail):

Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Dibutyl phthalate)
Hazard Class 9
UN Number: 3082
Packaging Group: 3

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 15 · REGULATORY INFORMATION

US FEDERAL REGULATIONS

Comprehensive Environmental Response and Liability Act (CERCLA)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. The reportable quantity (RQ) for this material is 1000 pounds. If appropriate, immediately report to the National Response Center (800/424-8802) as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies.

Toxic Substance Control Act (TSCA): All components of this product are listed on the TSCA inventory list.

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA Section 313 (40 CFR 372) Hazard Categories:

The following components are subject to reporting levels established by SARA Title III, Section 313: Dibutyl phthalate

Clean Water Act: This product contains Dibutyl phthalate a chemical listed as Hazardous Substances under the CWA

Clean Air Act: None of the chemicals in this product are listed as Hazardous Substances under the CCA.

California Prop 65: This product contains Dibutyl phthalate a chemical known by the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16 · OTHER INFORMATION

MSDS Revision Date: November 2014

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

Health: 0

Flammability: 1

Reactivity: 0

The information above is believed to be accurate and represents the best information currently available to us. However, Colonial Chemical Solutions makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Colonial be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Colonial has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this MSDS and its contents from that originally submitted by Colonial.