

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 1 - COMPANY AND PRODUCT IDENTIFICATION

PRODUCT

Product Name: MINERAL SPIRITS Rule 66
Control Number: 00091
Product Description: Dearomatized Hydrocarbons

COMPANY IDENTIFICATION

Supplier: COLONIAL CHEMICAL SOLUTIONS, INC.
916 West Lathrop Avenue
Savannah, Georgia 31415

24 Hour Emergency Telephone: (800)-424-9300 CHEMTREC
General Information: (912) 236-1331

SECTION 2- HAZARDS IDENTIFICATION

GHS Classification:

[Health]

Skin irritation Category 2
Aspiration hazard Category 1

[Environmental]

Chronic Aquatic Toxicity Category 2

[Physical]

Flammable Liquid Category 4

GHS Label elements, including precautionary statements

Pictograms



Signal Word: Danger

Hazard statement(s)

H227 Combustible liquid
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS Number	%WT
Petroleum Distillates Hydrotreated, light	64742-47-8	100

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 4 · FIRST AID MEASURES

FIRST AID PROCEDURES:

Eye Contact: Flush eyes with water. Seek medical attention if irritation persists..

Skin Contact: Remove contaminated clothing. Wash with soap and water.. Seek medical attention if irritation persists.

Inhalation: If inhaled, remove to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.

SECTION 5 · FIRE FIGHTING MEASURES

Suitable Extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous combustion products: Oxides of carbon and various hydrocarbons

Fire Fighting Procedures: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Unusual Fire and Explosion Hazards: Containers can build up pressure if exposed to heat and/or fire. Use water spray to keep fire-exposed containers cool. Containers may explode in the heat of a fire. Vapors will form an explosive mixture with air. Vapors will travel to a source of ignition and flash back.

SECTION 6 · ACCIDENTAL RELEASE and DISPOSAL MEASURES

Provide adequate ventilation. Evacuate all non-essential personnel from the spill area. Eliminate all ignition sources. Suitable protective clothing should be worn. Shut off or plug source of spill.

Small spills: absorb on inert media and collect into suitable container.

Large Spills: Dike spill area to contain liquid. Salvage as much re-useable liquid as possible into a suitable container. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations

SECTION 7 · STORAGE AND HANDLING

Handling: Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Keep container closed and tightly sealed when not in use. Avoid contact with skin and eyes.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Storage: This material is a static accumulator. Use non-sparking tools. Store in a cool, dry, ventilated area, away from incompatible substances. Store only in approved properly labeled containers. Containers should be grounded and bonded.

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. The level of protection and types of controls will vary depending upon potential exposure conditions.

Exposure Limits: Petroleum Distillate Hydrotreated 100 ppm ACGIH; 100 ppm OSHA

Personal Protective Equipment (PPE):

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133.

Skin: If prolonged or repeated skin contact is likely, wear appropriate protective gloves.

Clothing: Selection of protective clothing depends on work conditions, potential exposure conditions and may include gloves, boots, suits and other protective items.

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: 104 °F

Autoignition Temperature: 500 °F

Boiling Point Range: 322-380 °F

Melting Point/Freezing Point: No available data

Vapor Pressure: 2 mmHg

Vapor Density (Air-1): 4.9

Appearance/Odor: Clear colorless liquid with mild odor.

Flammability Limits: Lower: 1 Upper: 6

Specific Gravity: 0.776

Volatile %: > 95

Evaporation Rate (BuAc=1): 0.2

pH: Not Applicable

Solubility in Water: Negligible

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use and temperature conditions.

Conditions to Avoid: Keep away from heat, flame and other potential ignition sources. Temperatures in excess of 120 °F for prolonged periods.

Incompatible Materials: Strong oxidizing agents.

Hazardous Polymerization: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Signs and Symptoms of Overexposure:

Skin: Contact can cause redness and irritation. Severity depends on the amount and duration of exposure.

Eyes: Vapors are irritating to the eyes. Liquid contact will cause stinging and tearing.

Inhalation: Excessive inhalation of high concentrations may be harmful. Mist or vapor can irritate the throat and lungs.

Breathing this material may cause central nervous system depression.

Ingestion: If swallowed this material may irritate the mucous membranes of the mouth throat and esophagus. Aspiration of this material into the lungs may result in damage or death.

Acute oral toxicity:

LD50 rat: >3160 mg/kg

Acute inhalation toxicity:

LC50 rat: No available data

Acute dermal toxicity:

LD50 rabbit: No available data

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 12 · ECOLOGICAL INFORMATION

Aquatic Toxicity: Not expected to be harmful to aquatic organisms.

Bio-accumulative potential: Expected to be readily biodegradable.

Mobility: Accidental spillage may lead to penetration in the soil and contamination of groundwater.

SECTION 13 · DISPOSAL CONSIDERATIONS

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

SECTION 14 · TRANSPORTATION

U.S. DEPARTMENT OF TRANSPORTATION (Road or Rail):

Proper Shipping Name:	Petroleum Distillates, n.o.s.
Hazard Class	3
UN Number:	1268
Packaging Group:	3

SECTION 15 · REGULATORY INFORMATION

US FEDERAL REGULATIONS

Comprehensive Environmental Response and Liability Act (CERCLA)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. The reportable quantity (RQ) for this material is 1000 pounds. If appropriate, immediately report to the National Response Center (800/424-8802) as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies.

Toxic Substance Control Act (TSCA): All components of this product are listed on the TSCA inventory list.

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Fire Hazard, Acute Health Hazard

SARA Section 313 (40 CFR 372) Hazard Categories:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act: This product contains no chemicals that are listed under the CWA.

Clean Air Act: This product contains no chemicals that are listed under the CAA.

California Prop 65: This product contains no chemicals known by the State of California to cause cancer, birth defects or other reproductive harm.

SAFETY DATA SHEET



Colonial Chemical Solutions, Inc.

SECTION 16 · OTHER INFORMATION

MSDS Revision Date: September 2014

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

Health: 1

Flammability: 2

Reactivity: 0

The information above is believed to be accurate and represents the best information currently available to us. However, Colonial Chemical Solutions makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Colonial be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Colonial has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this MSDS and its contents from that originally submitted by Colonial.